Material Safety Data Sheet

Bona 3

MSDS #: 10012

0

0

24-Hour Emergency Telephone Number 1-800-424-9300 (Chemtree)

MSDS #: 10012

HMIS Ratings:

HEALTH:

DATE OF PREPARATION: 4/30/2001 LAST REVISION DATE: 4/10/2000 FLAMMABILITY:

REACTIVITY: 0

PROTECTION:

PRODUCT NAME:

BONA® SWEDISH FORMULA® HARDWOOD FLOOR REFRESHER

PRODUCT DESCRIPTION: WATERBORNE URETHANE WOOD FLOOR MAINTENANCE PRODUCT

RESEARCH FOR THE PROPERTY OF T

Occupational VAPOR Exposure Limits PRESSURE-INGREDIENT % WEIGHT ACGIH-TLV OSHA-PEL mm Hg CAS# DIPROPYLENE GLYCOL MONOMETHYL ETHER 34590-94-8 <2% 100 PPM 100 PPM 0.55 @ 25C DIPROPYLENE GLYCOL N-BUTYL ETHER 29911-28-2 <2% N/E N/E 0.06 @ 20C N-METHYL-2-PYRROLIDONE 872-50-4 <2% N/E N/E 1.00 @ 25C

可能利益。自由的共享的企業的企業的企業的企業的企業的企業的企業。

BOILING RANGE: >212F (100C)

EVAPORATION RATE: Slower than n-Butyl Acetate

% VOLATILE - WT: 90

DENSITY: 8.39 LBS/GAL (1.01KG/L)

VAPOR DENSITY: Heavier than air

SOLUBILITY IN WATER: Miscible

PRODUCT CHARACTERISTICS: White, milky liquid with sweet acrylic odor

FLAMMABILITY CLASSIFICATION: Non-Flammable

FLASH POINT: Over 200F (93C) PMCC

% OF VOL. OF FLAMMABLE LIMITS (Upper): N/A

(Lower): N/A

EXTINGUISHING MEDIA: Foam, Carbon Dioxide, Dry Chemical

UNUSUAL FIRE

Closed containers may explode (due to the build-up of steam pressure) when exposed to extreme heat.

EXPLOSION HAZARDS:

SPECIAL

Water may be used to cool closed containers to prevent pressure build-up.

FIREFIGHTING PROCEDURES:

Material Safety Data Sheet

MSDS#: 10012

24-Hour Emergency Telephone Number 1-800-424-9300 (Chemtrec)

Alexander.

EYE CONTACT: Non-toxic SKIN CONTACT: Non-toxic INHALATION: Non-toxic

INGESTION: May cause gastrointestinal irritation. If swallowed, drink 1 or 2 glasses of water to dilute.

PRIMARY ROUTES OF ENTRY: Ingestion and Dermal

REGULATORY Section 313 supplier notification: This product contains the following chemical(s) subject to the DATA:

reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40CFR 372: None. This product contains the following chemical(s) which are known to the state of California to cause cancer or to cause birth defects or other reproductive harm:

None.

TOXICITY INFO: No ingredients in this product are listed by OSHA, IARC or NTP as a carcinogen, teratogen,

mutagen, or as having toxic reproductive effects. See Section II for exposure limits. Not an eye irritant or dermal irritant; non-toxic by oral ingestion and inhalation under FHSA/CPSC guidelines.

24. A. M. C. A. L. M. C. M. C

STABILITY: Stable REACTIVITY WITH WATER: Will Not Occur

HAZARDOUS DECOMPOSITION

PRODUCTS:

None

HAZARDOUS POLYMERIZATION: Will Not Occur

INCOMPATIBILITY

(MATERIALS TO AVOID):

None Known

THE CHARLES OF THE PARTY OF THE

IN CASE MATERIAL IS RELEASED OR SPILLED: No special procedures required.

WASTE DISPOSAL:

Contaminated absorbent should be disposed of in accordance with local, state and federal

regulations.

SHIPPING INFORMATION:

Not regulated as a DOT hazardous material

SECULION TO EXPERIENCE TO THE SECULION

RESPIRATORY PROTECTION: Not required.

VENTILATION: Use adequate mechanical (general and/or local) ventilation to maintain exposure below TLV,

PROTECTIVE GLOVES:

Not necessary,

EYE PROTECTION:

Not necessary.

OTHER PROTECTIVE

Not necessary.

Bona Kemi U.S.A., Inc. * 14805 E. Moncrieff Place * Aurora, Colorado 80011-1207

EQUIPMENT:

2 of 3

Material Safety Data Sheet 24-Hour Emergency Telephone Number

1-800-424-9300 (Chemtree)

MSDS #: 10012

HYGIENIC PRACTICES:

Wash hands with soap and water before eating or using rest rooms.

Do not transfer contents to bottles or other unlabeled containers. Do not store in high temperature (above 100F or 38C) environment. Keep from freezing.

KEEP OUT OF THE REACH OF CHILDREN

KEY CODE

HMIS = Hazardous Materials Information System

- 0 = Minimal Hazard
- 1 = \$light Hazard
- 2 = Moderate Hazard
- 3 = Serious Hazard
- 4 = Severe Hazard
- N/A = Not Applicable
- N/E = Not Established
- ACGIH = American Conference of Governmental Industrial Hygienists
- OEL= Occupational Exposure Limits
- PEL = Permissible Exposure Limit = exposure limit to an airborne contaminant in a workday set by OSHA
- TLV = Threshold Limit Value = Time-weighted average concentration for a normal 8-hour workday without adverse effect.
- IARC = International Agency for Research on Cancer
- NTP = National Toxicology Program
- OSHA = Occupational Safety and Health Administration

For additional health and safety information, call the BonaKemi Compliance Department at (303) 371-1411.

The identities of ingredients are withheld as proprietary information. The information on this data sheet represents our best opinion as to the proper use and handling of this product under normal conditions, based upon information compiled from sources considered to be dependable. It is accurate and reliable to the best of our knowledge and belief, but is not guaranteed to be so. It is the user's responsibility to determine the suitability of this product for a specific purpose and to adopt such safety precautions as may be necessary. Any use of the product which is not in conformance with this data sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user.

BEFORE USING ANY PRODUCT, READ THE LABEL.